

NESCOAT[®] AKRIMAX ULTRA

Pure Acrylic, Glossy Exterior Paint

DESCRIPTION

NESCOAT[®] AKRIMAX ULTRA is a water-based, silicone-modified, pure acrylic resin-based exterior paint. It has a glossy and smooth finish.

APPLICATION AREAS

It can be used on all types of plastered surfaces (exposed concrete, aerated concrete, brick, concrete block), existing painted surfaces, and exterior thermal insulation systems.

ADVANTAGES

- Developed to withstand harsh weather conditions.
- Offers excellent durability due to its pure acrylic resin structure.
- Effective protection against water with high water impermeability.
- Has a self-cleaning property with rainwater.
- High UV resistance provides durability against sunlight.
- Its bright and vibrant colors are long-lasting.
- Prevents the formation of micro cracks due to its flexible structure.

SURFACE PREPARATION

The substrate must be even, clean, dry, and strong enough to support the application. The surface should be free of any substances such as dirt and dust that could hinder adhesion. On existing painted surfaces, blistered paint and plaster layers should be scraped off. If the surface is heavily soiled with dirt and dust, it should be washed with pressurized water. Newly plastered surfaces should be allowed to cure completely. Significant cracks and imperfections on the surface should be repaired with **NESCOAT** repair mortars to even out the surface. Once the surface is even and solid, apply **NESCOAT[®] EXPRIME** exterior primer in a single coat. After the primer application, wait at least 12 hours for the surface to dry before proceeding with the painting.

APPLICATION

NESCOAT[®] AKRIMAX ULTRA is ready to use. If necessary, dilute with up to 5% water; adding too much water may cause unevenness and coverage issues on the surface. The product should be applied in two coats using an exterior roller, brush, or spray method. Wait at least 6 hours between coats, depending on weather conditions. After application, hands and used tools should be thoroughly cleaned with plenty of water.

DRYING TIME

Surface drying time is 6 hours at 23°C and 50% relative humidity. Full drying time is 24 hours. Drying time shortens at higher temperatures and lengthens at lower temperatures.

CONSUMPTION

0.15 L/m² (for two coats)

It should be noted that the specified consumption rates may vary depending on surface and application conditions. A sample should be conducted for accurate consumption.

WARNINGS AND RECOMMENDATIONS

- During application and drying, the ambient temperature and surface temperature should be between +5°C and +35°C.
- Ensure that the product is not exposed to frost or precipitation until it is fully dry.
- Do not use on horizontal surfaces exposed to rain.

STORAGE AND SHELF LIFE

- Protect the product from direct sunlight and frost.
- Do not stack more than 4 buckets on top of each other.
- The shelf life is 3 years from the production date under proper storage conditions.
- Once opened, containers should be tightly sealed when not in use.

PACKAGING

15 L and 2.5 L plastic buckets

SAFETY PRECAUTIONS

- Use appropriate protective equipment (clothing, gloves, goggles, mask) during application.
- In case of skin contact, wash the affected area thoroughly with water.
- For more detailed information, refer to the Material Safety Data Sheet.

QUALITY CERTIFICATES

- Complies with the ISO 9001:2015 quality management standard.
- Complies with the TS 7847 building materials standard.
- Complies with the G Regulation.



TECHNICAL SPECIFICATIONS

| Feature | Value |
|-------------------------------|-------|
| Gloss | G2 |
| Dry Film Thickness | E2 |
| Particle Size | S1 |
| Water Vapor Transmission Rate | V2 |
| Water Transmission Rate | W3 |
| Crack Covering Property | A0 |
| Carbon Dioxide Permeability | C0 |

*The values mentioned above are valid for +23°C and 50% relative humidity.

LEGAL DISCLAIMER

The information in this document is based on NESCAOT's laboratory tests and field experiences. NESCAOT is not responsible for any adverse outcomes resulting from the use of the product outside its intended purpose or if the above-mentioned conditions are not followed.