

## NESCOAT<sup>®</sup> DRIP EDGE

### DESCRIPTION

**NESCOAT<sup>®</sup> Drip Edge** is an L-shaped PVC profile reinforced with fiberglass mesh. The primary function of drip profiles is to ensure the proper drainage of rainwater on exterior facades, preventing water from accumulating on the wall and damaging the surface (cracking, detachment, moisture).

### APPLICATION AREAS

Used on exterior facades, under building overhangs, and below balconies or roof parapet overhangs where no existing drip system is present.

### ADVANTAGES

- The mesh structure provides better adhesion to the plaster layer.
- Protects the facade from the negative effects of rainwater.
- Exhibits high resistance to alkalis.
- Perfectly compatible with system components.
- Offers a durable and long-lasting solution.

### APPLICATION

- After the anchoring process, the plaster mortar is applied to the corner areas using a steel trowel.
- The Drip Edge is pressed onto the mortar and positioned.
- The Drip Edge is carefully leveled with a steel trowel; if there is any misalignment, it should be corrected while the mortar is still wet.

### WARNINGS AND RECOMMENDATIONS

- The product should be stored in a cool, dry environment and protected from direct sunlight.
- Fiberglass may cause skin irritation upon contact; please use gloves during handling or application.

### TECHNICAL SPECIFICATIONS

Property	Value
Color	White
Packaging Type	Pack
Length	2.5 m
Package Quantity	25 pieces (62.5 m)
Edge Widths	7x7, 10x10