

NESCOAT® PREMIUM 75 Fiberglass Mesh

DESCRIPTION

NESCOAT® PREMIUM F75 is a fiberglass mesh produced by weaving glass fibers with specified mesh openings and coating them with styrene acrylic. This product is specially developed for waterproofing and thin plaster applications.

APPLICATION AREAS

- Used as a reinforcement mesh in waterproofing systems.
- Used for strengthening plaster surfaces and preventing cracks.

ADVANTAGES

- A high-performance fiberglass mesh.
- Provides excellent reinforcement in waterproofing systems.
- Effectively minimizes plaster cracks.
- Exhibits high resistance to alkalis.
- Perfectly compatible with system components.
- Offers a durable and long-lasting solution.

APPLICATION

- Apply the mortar to the surface using a notched steel trowel and comb it.
- Embed the fiberglass mesh into the plaster by pressing it lightly with a steel trowel from top to bottom.
- The fiberglass mesh should be placed evenly across the entire surface.
- Overlap the fiberglass mesh by 10 cm at the joints.
- At corners, turn the fiberglass mesh onto the surface of the adjacent edge.
- Apply the second layer of mortar before the first layer dries, and level the surface with a steel trowel.
- After application, wash hands and tools thoroughly with plenty of water.

WARNINGS AND RECOMMENDATIONS

- The product should be stored in a cool, dry environment and protected from direct sunlight.
- Fiberglass may cause skin irritation upon contact; please use gloves during handling or application.

QUALITY CERTIFICATES

- Complies with the ISO 9001:2015 quality management standard.
- CE marked, compliant with EU standards.



TECHNICAL SPECIFICATIONS

Property	Value
Weight	75 g/m ²
Mesh Size	4 mm x 4 mm
Color	White
Packaging Type	Rolls
Dimensions (Length x Width)	1m x 50m
Packaging Weight	3.75 kg (±5%)

*The values mentioned above are valid for +23°C and 50% relative humidity.