

## NESCOAT<sup>®</sup> SENTELUX

### Synthetic Gloss Paint

#### DESCRIPTION

NESCOAT<sup>®</sup> SENTELUX is a high-gloss topcoat paint based on alkyd binders.

#### APPLICATION AREAS

Suitable for use on wood, plaster, and metal surfaces in both interior and exterior applications.

#### ADVANTAGES

- Offers superior durability.
- Provides bright and vibrant colors with long-lasting performance.
- High UV resistance ensures durability against sunlight.
- Excellent coverage makes it effective for large areas.
- Easy to apply on surfaces.

#### SURFACE PREPARATION

The surface should be smooth, clean, dry, and strong enough to support the application. Remove dirt, dust, and any materials that may prevent adhesion. For previously painted surfaces, sand down any peeling paint and repair damaged areas with putty. Prime metal surfaces with NESCOAT<sup>®</sup> ANTIRUST anti-rust primer, and wood or other surfaces with a synthetic primer.

#### APPLICATION

Dilute NESCOAT<sup>®</sup> SENTELUX with synthetic thinner at a ratio of 10–15% by volume to achieve the desired consistency. Apply in two coats using a roller, brush, or spray gun. Allow 12 hours of drying time between coats.

#### DRYING TIME

Surface drying time is 3 hours at 23°C and 50% relative humidity. Full drying time is 12 hours. Drying time shortens at higher temperatures and lengthens at lower temperatures.

#### CONSUMPTION

0.13 L/m<sup>2</sup> (for two coats)

The specified consumption amounts may vary depending on the surface and application conditions. A sample application is recommended for accurate consumption measurement.

### **WARNINGS AND RECOMMENDATIONS**

- During application and drying, ensure the ambient and surface temperatures are between +5 °C and +35 °C.
- Keep away from heat, sparks, flames, and hot surfaces.
- Use appropriate protective equipment (clothing, gloves, goggles, mask) during application.
- In case of skin contact, wash the affected area thoroughly with plenty of water.
- Refer to the Material Safety Data Sheet (MSDS) for detailed information.

### **STORAGE AND SHELF LIFE**

- Protect the product from direct sunlight and frost.
- The shelf life is 3 years from the production date under proper storage conditions.
- Once opened, containers should be tightly sealed when not in use.

### **PACKAGING**

15 L and 2.5 L plastic buckets

### **QUALITY CERTIFICATES**

- Complies with the ISO 9001:2015 quality management standard.
- Complies with the TS 39 building materials standard.



### **LEGAL DISCLAIMER**

The information in this document is based on NESCAOT's laboratory tests and field experiences. NESCAOT is not responsible for any adverse outcomes resulting from the use of the product outside its intended purpose or if the above-mentioned conditions are not followed.