

NESCOAT® CLEARCOAT

Transparent Protective Coating

DESCRIPTION

NESCOAT® CLEARCOAT is a water-based, silicone-modified, pure acrylic resin-based transparent coating. It forms a slightly glossy and transparent protective layer on surfaces.

APPLICATION AREAS

It is used for protecting and enhancing the appearance of exterior stones, concrete, and natural or artificial coatings without altering their natural look.

ADVANTAGES

- Preserves the natural appearance of the surface.
- Provides effective protection against water with high water resistance.
- Resistant to UV rays, ensuring durability under sunlight.
- Prevents micro-cracks with its flexible structure.
- Easy to apply on surfaces.

SURFACE PREPARATION

The substrate must be even, clean, dry, and strong enough to support the application. The surface should be free of any substances such as dirt and dust that could hinder adhesion. If the surface is heavily soiled with dirt and dust, it should be washed with pressurized water. Newly plastered surfaces should be allowed to cure completely. Significant cracks and surface irregularities should be repaired with NESCOAT repair mortars and leveled.

APPLICATION

NESCOAT® CLEARCOAT is ready to use and only needs to be mixed until a homogeneous consistency is achieved. The product should be applied in two coats using an exterior roller, brush, or spray method. Allow a minimum of 3 hours between coats, depending on weather conditions. After application, wash hands and tools thoroughly with plenty of water.

DRYING TIME

- Surface drying time is 6 hours at 23°C and 50% relative humidity.
- Full drying time is 24 hours.
- Drying time shortens at higher temperatures and lengthens at lower temperatures.

CONSUMPTION

0.1 L/m² (for two coats)

The specified consumption amounts may vary depending on the surface and application conditions. A sample application is recommended for accurate consumption measurement.

WARNINGS AND RECOMMENDATIONS

- During application and drying, the ambient temperature and surface temperature should be between +5°C and +35°C.
- Ensure that the product is not exposed to frost or precipitation until it is fully dry.
- Do not use on horizontal surfaces exposed to rain.

STORAGE AND SHELF LIFE

- Protect the product from direct sunlight and frost.
- Do not stack more than 4 buckets on top of each other.
- The shelf life is 3 years from the production date under proper storage conditions.
- Once opened, containers should be tightly sealed when not in use.

PACKAGING

15 L and 2.5 L plastic buckets

SAFETY PRECAUTIONS

- Use appropriate protective equipment (clothing, gloves, goggles, mask) during application.
- In case of skin contact, wash the affected area thoroughly with water.
- For more detailed information, refer to the Material Safety Data Sheet.

QUALITY CERTIFICATES

- Complies with the ISO 9001:2015 quality management standard.
- Complies with the TS 7847 building materials standard.
- Complies with the G Regulation.



TECHNICAL SPECIFICATIONS

Feature	Value
Gloss	G2
Dry Film Thickness	E2
Particle Size	S1
Water Vapor Transmission Rate	V2
Water Transmission Rate	W3
Crack Covering Property	A0
Carbon Dioxide Permeability	C0

*The values mentioned above are valid for +23°C and 50% relative humidity.

LEGAL DISCLAIMER

The information in this document is based on NESCAOT's laboratory tests and field experiences. NESCAOT is not responsible for any adverse outcomes resulting from the use of the product outside its intended purpose or if the above-mentioned conditions are not followed.