

NESCOAT® CURE A

Acrylic Emulsion-Based Curing Compound

DESCRIPTION

NESCOAT®CURE A is an acrylic emulsion-based curing compound. It forms a film layer on the surface after the application of concrete, screed, and cement-based surface hardeners, preventing the rapid evaporation of mixing water. This reduces shrinkage and minimizes the risk of cracking.

APPLICATION AREAS

- Suitable for indoor and outdoor use on fresh concrete, screed, and cement-based surface-hardened floors.
- Provides an effective solution for concrete casting and general concrete curing under conditions of low humidity, high evaporation, and air circulation.

ADVANTAGES

- Reduces water evaporation for effective curing.
- Enhances the durability and strength of the concrete surface.
- Provides a harder, dust-free surface.
- Easy to apply.

USAGE

- The product is ready to use. Shake well before application and apply using a spray, roller, or brush.
- Apply when the concrete surface has not completely dried, begins to lose its sheen, and becomes walkable.

WARNINGS AND RECOMMENDATIONS

- During application, the ambient and surface temperatures should be between +5 °C and +35 °C.
- Protect the product from direct sunlight and frost.
- Shelf life is 2 years from the production date if stored under proper conditions.
- Use appropriate protective equipment (gloves, goggles, mask) during application.
- In case of contact with skin, wash the affected area thoroughly with water.

TECHNICAL SPECIFICATIONS

Chemical Composition	Styrene Acrylic Emulsion
Appearance	White Liquid
Density	1.1 ± 0.1 g/cm ³
Packaging	5 and 20 kg plastic containers