

NESCOAT[®] SEALBAND

Waterproofing Tape for Wall and Floor Joints

DESCRIPTION

NESCOAT[®] SEALBAND is a synthetic rubber-based waterproofing tape with a polyester felt carrier. It is designed to provide effective waterproofing at movement joints and wall-to-floor intersections in wet areas.

APPLICATION AREAS

- Applied indoors and outdoors, on horizontal and vertical surfaces, such as concrete, plaster, screed, gypsum, or cement-based prefabricated panel surfaces, to protect against positive water pressure (on the water-facing surface).
- Used as waterproofing under tile coverings in water-exposed areas such as bathrooms, toilets, balconies, and terraces.

ADVANTAGES

- Ensures excellent compatibility even on moving surfaces.
- Practical and quick to apply.
- Compatible with all liquid-applied waterproofing materials and does not require special adhesives.
- Provides 100% watertightness.
- Resistant to most chemical substances.

APPLICATION

- Apply a thin layer of liquid-applied waterproofing material to the area where the waterproofing tape will be used.
- Carefully place the waterproofing tape at wall-to-floor intersections while the waterproofing material is still wet.
- Press firmly with a spatula or hand to ensure there are no air bubbles under the tape.
- Apply a second layer of waterproofing material over the tape.
- Both sides of the tape should be covered with waterproofing material, extending at least 2-3 cm on each side.

WARNINGS AND RECOMMENDATIONS

- Shelf life is 3 years from the production date under proper storage conditions.

TECHNICAL SPECIFICATIONS

System Width	120 mm
Water Pressure Resistance	2 bar
Packaging	10 m and 50 m rolls